

Claims

What is claimed is:

SLWD AM

5 1. A method for handling multiple data streams in a disc drive, the method comprising steps of:

- a) allocating a buffer size required by each data stream currently being handled;
- b) utilizing the buffer sizes found in allocating step a) for corresponding data streams;
- c) when an additional data stream is to be added, reallocating the buffer size required by each data stream including the additional data stream; and
- 10 d) when a data stream currently being handled is to be terminated, reallocating the buffer size required by each data stream that will remain after the data stream is terminated.

15 2. The method of claim 1, wherein the allocating step a) comprises a step of:

- a)(1) scaling a host data rate for each data stream by an expression for a total time to fill or empty the buffer size allocated to all of the data streams being handled to create a set of simultaneous equations for the buffer sizes; and
- a)(2) solving the simultaneous equations to find the buffer size to be allocated for each data stream.

20 3. The method of claim 2, wherein the scaling step a)(1) comprises a step of:

- a)(1)(A) summing an expression for time to fill or empty the buffer size to be allocated for each data stream with a time to sequentially switch between each data stream to find the expression of total time to fill or empty the buffer size allocated to all of the data streams being handled.

25 4. The method of claim 3, wherein the summing step a)(1)(A) comprises a step of:

- a)(1)(A)(i) scaling a variable for the buffer size to be allocated for the first data stream by a disc rate assigned for the first data stream to find the expression for the time to fill or empty the buffer size to be allocated for the first data stream.

-14-

5. The method of claim 1, further comprising a step of:
e) comparing a sum of the buffer size dedicated for each data stream to the total
buffer size available for use; and
f) detecting whether handling of the multiple data streams at a requested host data
5 rate and disc data rate is possible from a result of comparing step e).

6. The method of claim 1, further comprising:
h) receiving, by the disc drive, one or more of the data streams; and
i) sending, by the disc drive, one or more of the data streams.

10 7. The method of claim 1 wherein a sum of buffer sizes allocated for the data streams
is less than the total size of the buffer of the disc drive.

15 8. The method of claim 1, further comprising:
j) receiving, by the disc drive, data not in a stream; and
k) sending, by the disc drive, data not in a stream.

-15-

9. A disc drive for handling multiple data streams, comprising:
one or more discs that store data;
a buffer that outputs data streams to the one or more discs and receives data streams from
the one or more discs; and

5 a processor in electrical communication with the buffer, the processor being configured to
dynamically allocate the size of the buffer used for each data stream being handled by the disc
drive by computing a buffer size required by each data stream currently being handled,
instructing the buffer to utilize the buffer sizes for corresponding data streams, recomputing the
buffer size allocated to each data stream including an additional data stream when an additional
10 data stream is to be added, and when a data stream will be terminated, recomputing the buffer
size allocated to each data stream that will remain after a data stream is terminated.

15 10. The disc drive of claim 9, wherein the processor is configured to compute the
buffer size required by each data stream currently being handled by scaling a host data rate for a
first stream by an expression for a total time to fill or empty the buffer size dedicated to all of the
data streams being handled to create a set of simultaneous equations for the buffer sizes and is
further configured to solve the simultaneous equations to find the buffer size for each data
stream.

20 11. The disc drive of claim 10, wherein the processor is configured to sum an
expression for a time to fill or empty the buffer size to be dedicated for each data stream with a
time to sequentially switch between each data stream to find the total time to fill or empty the
buffer size dedicated to all of the data streams being handled.

25 12. The disc drive of claim 11, wherein the processor is configured to scale a variable
for the buffer size to be dedicated for the first data stream by a disc rate assigned for the first data
stream to find the expression for the time to fill or empty the buffer size to be dedicated for the
first data stream.

30 13. The disc drive of claim 9, wherein the processor is further configured to compare a
sum of the buffer sizes dedicated for each data stream to the total buffer size available for use,

-16-

and detect whether handling of the multiple data streams at a requested host data rate and disc data rate is possible from a result of the comparison.

AM

14. The disc drive of claim 9, wherein one or more of the data streams are received
5 into the buffer at a host rate and are recorded to the disc at a disc rate, and wherein one or more of
the data streams are received into the buffer at a second disc rate and are sent from the buffer at a
second host rate.

15. The disc drive of claim 9, wherein the processor is configured to compute a sum
10 of buffer sizes allocated for the data streams that is less than the total size of the buffer of the disc
drive.

16. The disc drive of claim 9, wherein data not in a stream is received into the buffer
and is recorded to the disc, and wherein data not in a stream is received into the buffer and is sent
15 from the buffer contemporaneously with the buffer utilizing the buffer sizes allocated by the
processor.

T002500 07/16/05

-17-

17. A disc drive for handling multiple data streams, comprising:
a buffer that receives data from the multiple data streams; and
means for reallocating an amount of the buffer required for each data stream being
handled whenever a new data stream is added or an existing data stream is terminated.

5

18. The disc drive of claim 17, wherein the means for reallocating is configured to
compute an amount of the buffer required by each data stream currently being handled by scaling
a host data rate for a first stream by an expression for a total time to fill or empty the buffer
amount dedicated to all of the data streams being handled to create a set of simultaneous
10 equations for the buffer amounts and that is further configured to solve the simultaneous
equations to find the buffer amount for each data stream.

10

15 19. The disc drive of claim 18, wherein the means for reallocating is configured to
sum an expression for a time to fill or empty the buffer amount to be dedicated for each data
stream with a time to sequentially switch between each data stream to find the total time to fill or
empty the buffer amount dedicated to all of the data streams being handled.

15

20 20. The disc drive of claim 19, wherein the means for reallocating is configured to
scale a variable for the buffer amount to be dedicated for the first data stream by a disc rate
assigned for the first data stream to find the expression for the time to fill or empty the buffer
amount to be dedicated for the first data stream.

20

25 21. The disc drive of claim 17, wherein the means for reallocating is further
configured to compare a sum of the buffer amounts dedicated for each data stream to the total
buffer amount available for use, and detect whether handling of the multiple data streams at a
requested host data rate and disc data rate is possible from a result of the comparison.

25

30 22. The disc drive of claim 17, wherein one or more of the data streams are received
into the buffer at a host rate and are recorded to the disc at a disc rate, and wherein one or more of
the data streams are received into the buffer at a second disc rate and are sent from the buffer at a
second host rate.

SEARCHED
INDEXED
SERIALIZED
FILED

-18-

23. The disc drive of claim 18, wherein the means for reallocating is configured to compute a sum of buffer amounts allocated for the data streams that is less than the total size of the buffer of the disc drive.

5 24. The disc drive of claim 18, wherein data not in a stream is received into the buffer and is recorded to the disc, and wherein data not in a stream is received into the buffer and is sent from the buffer contemporaneously with the buffer utilizing the buffer amounts allocated by the means for reallocating.